

What is claimed is:

1. A device for measuring ionic activity which  
5 comprises:

a block of insulating material having a hollow space  
therein, a solution-receiving surface area in which a  
pair of openings for receiving a sample solution and a  
reference solution separately are provided, said openings  
10 connecting with the hollow space, a plurality of solu-  
tion-supplying surface areas in each of which a pair of  
openings for supplying outside the sample solution and  
the reference solution separately are provided, said  
openings connecting with the hollow space;

15 a bridge member provided on the solution-receiving  
surface area for electrically bridging the sample solu-  
tion received in one opening and the reference solution  
received in another opening;

a guide member placed in the hollow space which as-  
20 sists to transmit separately the sample solution received  
in the opening in the solution-receiving surface area to  
the openings on the solution-supplying surface areas for  
the supplying outside the sample solution and the refer-  
ence solution received in the opening in the solution-  
25 receiving surface area to the openings on the solution-  
supplying surface areas for the supplying outside the  
reference solution;

and

a plurality of ion selective electrodes having an  
30 ion selective membrane thereon each of which is placed on  
the solution-supplying surface area under such condition  
that the ion selective membrane is brought into contact  
with the sample solution and the reference solution sepa-  
rately.

35

2. The device of claim 1, wherein the guide member is a partition which is placed in the hollow space to guide separately the sample solution and the reference solution.

5

3. The device of claim 1, wherein the guide member comprises a pair of porous liquid-transmitting materials placed in the hollow space, one of which transmits the sample solution and another of which transmits the reference solution.

10

4. The device of one of claim 1, wherein the block is in the form of a rectangular parallelepiped having a upper surface on which the solution-receiving surface area is arranged, and other surfaces including a bottom surface and side surfaces on at least two of which the solution-supplying surface area is arranged.

15

5. The device of one of claim 1, wherein the block is in the form of a horizontally extended rectangular parallelepiped having a upper surface on which the solution-receiving surface area is arranged, a bottom surface, and side surfaces, the plurality of the solution-supplying surface areas are arranged on at least one of these surfaces.

20

25

6. The device of claim 1, wherein the block is in the form of a vertically extended rectangular parallelepiped having a upper surface on which the solution-receiving surface area is arranged, and other surfaces including a bottom surface and side surfaces on at least two of which the solution-supplying surface area is arranged.

30

35

T09027-643004

2. The device of claim 1, wherein the guide member is a partition which is placed in the hollow space to guide separately the sample solution and the reference solution.

5

3. The device of claim 1, wherein the guide member comprises a pair of porous liquid-transmitting materials placed in the hollow space, one of which transmits the sample solution and another of which transmits the reference solution.

10

4. The device of claim 1, wherein the block is in the form of a rectangular parallelepiped having a upper surface on which the solution-receiving surface area is arranged, and other surfaces including a bottom surface and side surfaces on at least two of which the solution-supplying surface area is arranged.

15

5. The device of claim 1, wherein the block is in the form of a horizontally extended rectangular parallelepiped having a upper surface on which the solution-receiving surface area is arranged, a bottom surface, and side surfaces, the plurality of the solution-supplying surface areas are arranged on at least one of these surfaces.

20

25

6. The device of claim 1, wherein the block is in the form of a vertically extended rectangular parallelepiped having a upper surface on which the solution-receiving surface area is arranged, and other surfaces including a bottom surface and side surfaces on at least two of which the solution-supplying surface area is arranged.

30

35